

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)  
CB SCHEME

## CB TEST CERTIFICATE

Product

Switch Mode Power Supply

Name and address of the applicant

VOX POWER LTD  
Unit 2  
Redcow Interchange Estate  
Dublin, 22 Ireland

Name and address of the manufacturer

VOX POWER LTD  
Unit 2  
Redcow Interchange Estate  
Dublin, 22 Ireland

Name and address of the factory

Panyu Trio Microtronics Co Ltd  
SHIJI INDUSTRIAL ESTATE  
DONGYONG  
NANSHA  
GUANGZHOU, 511453 GUANGDONG China

Note: When more than one factory, please report on page 2

 Additional Information on page 2

Ratings and principal characteristics

See Page 2

Trademark / Brand (if any)

VOX POWER



Type of Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

VCCM600S-abcd-zzzz  
See Page 2

Additional information (if necessary may also be reported on page 2)

 Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

E316486-A6003-CB-1 issued on 2020-02-24

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2020-02-24

Signature:

Jan-Erik Storgaard



Ref. Certif. No.

**DK-93519-UL**

**Model Details:**

VCCM600S-abcd-zzzz where abcd is optional and denotes respectively slot 1, slot 2, slot 3, slot 4 and each may be as follows: 0, A, B, C, or D; zzzz may be blank or alphanumeric characters.

**Output modules:**

OPA; OPB; OPC; OPD

**Ratings:**

VCCM600S-abcd-zzzz input rating:

100-240 V ac, 7 A, 50-60 Hz

Maximum output power is 600 W.

Individual outputs rated according to modules fitted.

Output modules output ratings (optional):

OPA = 1.5 - 7.5 V dc, 25 A, 125 W

OPB = 4.5 - 15 V dc, 15 A, 150 W

OPC = 9 - 30 V dc, 7.5 A, 150 W

OPD = 18 - 58 V dc, 3.75 A, 150 W

All output modules current and power ratings are the maximum allowable.

**Additional Information:**

Additionally evaluated to EN 62368-1:2014 / A11: 2017; National Differences specified in the CB Test Report.

**Additional information (if necessary)**



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2020-02-24

Signature:

Jan-Erik Storgaard