Ref. Certif. No.

DK-182509-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Switch Mode Power Supply
Name and address of the applicant	VOX POWER LTD Unit 2, Redcow Interchange Estate, Ballymount Dublin D22 Y8H2 Ireland
Name and address of the manufacturer	VOX POWER LTD Unit 2, Redcow Interchange Estate, Ballymount Dublin D22 Y8H2 Ireland
Name and address of the factory Note: *When more than one factory, please report on page 2*	Trio-Tronics (Thailand) Ltd 7/295 Mu. 6, Map Yang Phon Sub-District Pluak Daeng District, Rayong, Thailand ☒ Additional Information on page 2
Ratings and principal characteristics	Input rating: 100-240 V ac, 7 A, 50-60 Hz ☒ Additional Information on page 2
Trademark / Brand (if any)	VOX POWER
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	VCCM600S-abcd-zzz ☒ Additional Information on page 2
Additional information (if necessary may also be reported on page 2)	Evaluated to National or Group Differences for CA, EU Group Differences, JP, CH, US ☒ Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2023
As shown in the Test Report Ref. No. which forms part of this Certificate	E316486-A6014-CB-1 issued on 2026-06-26

This CB Test Certificate is issued by the National Certification Body

UL Solutions

☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
☒ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
☐ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2026-06-26

Signature:
Thomas Wilson

Factory(ies):
Panyu Trio Microtronics Co Ltd
SHIJI INDUSTRIAL ESTATE, DONGYONG, NANSHA GUANGZHOU, Guangdong, 511453
China

Additional Model Detail(s):
VCCM600S-abcd-zzzz, where abcd is optional and denotes respectively slot 1, slot 2, slot 3, slot 4 and each may be as follows: 0, A, B, C, or D. zzzz may be blank or alphanumeric characters.

Output modules:
OPA; OPB; OPC; OPD

Additional Ratings:

Maximum output power is 600 W.
Individual outputs rated according to modules fitted.
Output modules output ratings (optional):
OPA = 1.5 - 7.5 V dc, 25 A, 125 W
OPB = 4.5 - 15 V dc, 15 A, 150 W
OPC = 9 - 30 V dc, 7.5 A, 150 W
OPD = 18 - 58 V dc, 3.75 A, 150 W
All output modules current and power ratings are the maximum allowable.
Evaluated to National Differences declared for:
EN IEC 62368-1:2024, EN IEC 62368-1:2024/A11:2024

Additional information (if necessary)

☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
☒ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
☐ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2026-06-26

Signature:

Thomas Wilson